

1	LABKO FRW DIRECT	NS	3	6	10	15	20	30
	Nominal flow rate	l/s	3	6	10	15	20	30
A	Inlet pipe	D	110	160	160	200	250	250
B	Outlet pipe	D	110	160	160	200	250	250
C	Flow regulator	pcs	1	1	1	1	1	1
D	EuroHUK 800 maintenance shaft (as needed)	pcs	1	1	1	1	1	1
E	Cast iron cover D400 (40 tn) [ ] (accessory)	pcs	1	1	1	1	1	1
F	Ventilation outlet D110	pcs	1	1	1	1	1	1
$h_{min}$	Min. connection height	mm	1300	1300	1300	1300	1300	1300
$h_{max}$	Max. connection height	mm	2900	2900	2900	2900	2900	2900
	Material		PEM	PEM	PEM	PEM	PEM	PEM
	Chosen LABKO FRW DIRECT	(x)	[ ]	[ ]	[ ]	[ ]	[ ]	[ ]

Selection of maintenance shaft EuroHUK 800 for FRW DIRECT NS3-NS30				
EuroHUK 800 maintenance shaft model	9-13 [ ]	13-17 [ ]	17-21 [ ]	21-25 [ ]
Installation depth of the inlet sewer from ground surface	1300-1700	1700-2100	2100-2500	2500-2900


**Note! SPECIAL MODEL without by-pass**

$h$  = Separator connection height from ground (mm)

$h$  = \_\_\_\_\_ mm

This drawing and the technical information included in the drawing are property of Wavin-Labko Ltd. Authorities' regulations must be known before providing the product. Products must be installed according to installation instructions.



Product: <b>LABKO FRW DIRECT NS3-NS30</b>			Drawing type: <b>Customer Drawing</b>	
Design by: JP/MaL	Approved by: JP 26.11.2008	Drawing no: 42CB02_e	Date: 28.10.2008	Scale (A4): 1:30
			Construction site: WAVIN-LABKO Ltd. Labkotie 1 FIN-36240 KANGASALA FINLAND puh. +358 020 1285 200 fax. +358 0201285 280	